

**高强高模聚乙烯醇纤维 W2
(超短纤)**

分子式: $(\text{CH}_2\text{CHOH})_n$

质量标准: 纤度: $2.0\pm 0.25\text{dtex}$

强度: $\geq 12.80\text{CN/dtex}$

伸度: $\leq 7\%$

模量 (0.1-0.4%): $\geq 290\text{CN/dtex}$

热水减量 (90°C, 1 小时): $\leq 2\%$

比重: 1.29

切断长度: 4mm, 5mm, 6mm

包 装: 180 公斤净重塑编袋 (1000×550×600mm)
12.96 吨/20'FCL 集装箱

用 途: 石棉代用品;
用于建材、混凝土等领域;
可用做塑料、橡胶的增强纤维。

安徽皖维高新材料股份有限公司

地址: 中国安徽省巢湖市皖维路 56 号 国际贸易部

电话: 0551-82189233

传真: 0551-82317233

邮政编码: 238002

**HIGH STRENGTH AND HIGH MODULUS
POLYVINYL ALCOHOL FIBER W2 (OVERSHOTR)**

Formula: $(\text{CH}_2\text{CHOH})_n$

Quality Standard: Count: $2.0\pm 0.25\text{dtex}$

Tenacity: $\geq 12.80\text{CN/dtex}$

Elongation: $\leq 7\%$

Molulus (0.1-0.4%): $\geq 290\text{CN/dtex}$

Hot Water Solubility(90°C, 1hour): $\leq 2\%$

Density: 1.29

Cut Length: 4mm, 5mm, 6mm

Packing: P.P. bag, 180kg net weight
(1000×550×600mm)

12.96T/20'FCL Container

Uses: It is the best substitution of asbestos, used in the building material industry, concrete industry and so. It also can increase intensity of plastic and rubber.

ANHUI WANWEI UPDATED HIGH-TECH MATERIAL
INDUSTRY COMPANY LIMITED

Add: No. 56 Wanwei Road, Chaohu City, Anhui Province, China

Tel: 0551-82189233

Fax: 0551-82317233

Post Code: 238002