

全国功能高分子行业委员会 上海宇昂水性新材料科技股份有限公司

China Functional Polymer Industry Committee Shanghai Yuking Water Soluble Material Tech Co.,Ltd

MATERIAL SAFETY DATA SHEET

Issue Date: Jan. 01, 2010

Last Review Date: Jan. 01, 2023

Section 1. Chemical Product and Company Identification

Product Name: POVIDONE K30 USP43; PVP K30 USP26, Polyvinylpyrrolidone

CAS NO.: 9003-39-8

Chemical Name: Poly(1-vinyl-2-pyrrolidinone)

Chemical Formula: (C6H9NO)n

Contact information:

Shanghai Yuking Water Soluble Material Tech Co.,Ltd 4F, 13B, South Xinyuan Rd, 201306, Shanghai, China

CHEMTREC (24HR Emergency Telephone), call: +86-21-68286255

For non-emergency assistance, call: +86-21-68286299

Section 2. Hazards Identification

Classification

This chemical is not considered hazardous according to the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

This chemical is considered hazardous according to the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Label elements

Not classified warning

May from combustible dust concentrations in air

Hazards not otherwise classified (HNOC)

Not Applicable

Other hazards

Not available

Precautionary Statements - Prevention

Keep away from all ignition sources including heat, sparks, and flame

Keep container closed and grounded

Prevent dust accumulations to minimize explosion hazard

地址:上海市浦东新区临港泥城新元南路600号13B4楼 Address: 4F, 13B, South Xinyuan Rd, 201306, Shanghai, China Tel: +86-21-68286208 Fax: +86-21-68286226 http://www.yukinggroup.com



全国功能高分子行业委员会 上海宇昂水性新材料科技股份有限公司

China Functional Polymer Industry Committee Shanghai Yuking Water Soluble Material Tech Co., Ltd

Section 3. Composition and Information on Ingredients

Composition:

Name	CAS#	%by weight
POVIDONE K	9003-39-8	100

Section 4. First Aid Measures

Eye Contact: Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops. Cold water may be used.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation: Not available.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

Serious Ingestion: Not available.

Section 5. Fire Fighting Measures

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: Not available.

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: These products are carbon oxides (CO, CO2), nitrogen oxides (NO,

NO2...).

Fire Hazards in Presence of Various Substances:

Slightly flammable to flammable in presence of heat. Non-flammable in presence of shocks.

Explosion Hazards in Presence of Various Substances:

Slightly explosive in presence of open flames and sparks. Non-explosive in presence of shocks.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards: As with most organic solids, fire is possible at elevated temperatures

Special Remarks on Explosion Hazards:

地址:上海市浦东新区临港泥城新元南路600号13B4楼 Address: 4F, 13B, South Xinyuan Rd, 201306, Shanghai, China Tel: +86-21-68286208 Fax: +86-21-68286226 http://www.yukinggroup.com



全国功能高分子行业委员会 上海宇昂水性新材料科技股份有限公司 China Functional Polymer Industry Committee

Shanghai Yuking Water Soluble Material Tech Co.,Ltd

Fine dust dispersed in air in sufficient concentrations, and in the presences of an ignition source is a potential dust explosion hazard.

Section 6. Accidental Release Measures

Small Spill: Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill: Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system.

Section 7. Handling and Storage

Precautions:

Keep away from heat. Keep away from sources of ignition. Do not ingest. Do not breathe dust. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area.

Section 8. Exposure and Protection Controls

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: Not available.

Section 9. Physical and Chemical Properties

Physical state and appearance: Solid. (Powdered solid.)

Odor: Odorless.

Taste: Not available.

Molecular Weight: (111.14)n g/mole

Color: Creamy White.

pH (1% soln/water): Not available.

Melting Point: 130°C

Critical Temperature: Not available.

地址:上海市浦东新区临港泥城新元南路600号13B4楼 Address:4F, 13B, South Xinyuan Rd, 201306, Shanghai, China Tel:+86-21-68286208 Fax:+86-21-68286226 http://www.yukinggroup.com



全国功能高分子行业委员会 上海宇昂水性新材料科技股份有限公司

China Functional Polymer Industry Committee Shanghai Yuking Water Soluble Material Tech Co.,Ltd

Specific Gravity: Density: 1.23 - 1.29(Water = 1)

Vapor Pressure: Not applicable. Vapor Density: Not available. Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist.

Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: See solubility in water.

Solubility:

Soluble in cold water. Soluble in water giving a colloidal solution. Soluble in chloroform, alcohol, chlorinated hydrocarbons, amines, nitro pariffins, lower weight fatty acids.

Section 10. Stability and Reactivity

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Excess heat, incompatible materials Incompatibility with various

substances: Reactive with oxidizing agents. Corrosivity: Not available.

Special Remarks on Reactivity: Hygroscopic; keep container tightly closed.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11. Toxicological information

Routes of Entry: Inhalation. Ingestion.

Toxicity to Animals: Acute oral toxicity (LD50): 40000 mg/kg [Mouse].

Chronic Effects on Humans: CARCINOGENIC EFFECTS: 3 (Not classifiable for human.) by

IARC.

Other Toxic Effects on Humans: Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: It is not considered a primary irritant. However, it may cause skin irritation. Eyes: May cause eye irritation. Inhalation: Breathing dust may cause respiratory tract irritation. Symptoms may include coughing, sore throat, labored breathing, and chest pain. Ingestion: May cause gastrointestinal tract irritation with nausea, vomiting,

hypermotility, and diarrhea. Chronic Potential Health Effects: Ingestion: Prolonged or repeated ingestion may affect the urinary system, and spleen.

地址:上海市浦东新区临港泥城新元南路600号13B4楼 Address: 4F, 13B, South Xinyuan Rd, 201306, Shanghai, China Tel: +86-21-68286208 Fax: +86-21-68286226 http://www.yukinggroup.com



全国功能高分子行业委员会 上海宇昂水性新材料科技股份有限公司 China Functional Polymer Industry Committee

China Functional Polymer Industry Committee Shanghai Yuking Water Soluble Material Tech Co., Ltd

Section 12. Ecological Information

Ecotoxicity: Not available. BOD5 and COD: Not available. Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13. Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14. Transport Information

DOT Classification: Not a DOT controlled material (United States).

IMDG Classification: Not a dangerous goods IATA Classification: Not a dangerous goods

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

Section 15. Other Regulatory Information

European information

Caution: substance not yet fully tested.

Section 16. Other information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Our company shall not be held liable for any damage resulting from handling or from contact with the above product.

地址: 上海市浦东新区临港泥城新元南路600号13B4楼 Address: 4F, 13B, South Xinyuan Rd, 201306, Shanghai, China Tel: +86-21-68286208 Fax: +86-21-68286226 http://www.yukinggroup.com