

Powder & Granular Wood Based Activated Carbon

Mobile : +91 8799335345

Email : quotation@ecofriendcarbon.com

EcoFriend Carbon Pvt. Ltd.

Web: www.ecofriendcarbon.com

Material Safety Data Sheet

Section 1 – Identification of the Substance / Preparation, and of the Company

1.1: Product Identifier

Trade Name: Wood Based Activated Carbon

Substance Name: Activated Carbon, CAS 7442-44-0 EC Number: 231-153-3

1.2: Identified uses of the substance or mixtures

- 1.2.1 Uses: Inorganic source of carbon, filler, liquid and/or gaseous adsorption trains, decolorization, Filtration, other processes and applications compatible with cellulosic-based activated carbon.
- 1.2.2 Uses Advised Against: For industrial use only, not for food, drug, or cosmetic applications.

1.3: Supplier Information

Company/Manufacturer: EcoFriend Carbon Pvt. Ltd.

Survey No. 676. Opp. Dada Bhagvan Temple,

Surendranagar - Rajkot Highway, Surendranagar Gujarat - 363020

Telephone: +91-8799335345

Email Address: quotation@ecofriendcarbon.com

Date Prepare: 15 November, 2022

1.4: Emergency Telephone Number

Contact No. - 8799335345

Section 2: Hazards Identification

2.1: Classification of substance

Wood based activated carbon is not a hazardous substance.



Based Activated Carbon

EcoFriend Carbon Pvt. Ltd.

Mobile : +91 8799335345

Email : quotation@ecofriendcarbon.com
Web : www.ecofriendcarbon.com

2.2: Label Elements

Wood based activated carbon is not a hazardous substance, no labelelements are required

Section 3 – Composition/Information on Ingredients:

Chemical Composition: Wood Based

Activated Carbons 100%

CAS # 7440-44-0 EC # 264-864-4

Molecular Weight: 12.0

Section 4 - First Aid Measures

Jection + 1	iist Alu ivicasui es		
4.1.1	Remove patient to particulate-free environment. Wear approved dust mask to Inhalation avoid breathingdust. Seek medical attention if irritation persists.		
4.1.2 Skin Contact	Wash with mild soap and warm water: Wood Based activated carbon is not chemical irritant.		
4.1.3 Eye Contact possible.	Rinse with tepid water until eyes are clear of particulates. Seek medical attention if irritation persists. Mechanical/abrasion related irritation is		
4.1.4 Medical Ingestion	Get immediate medical attention. Do not induce vomiting unless directed by personnel.		
	Wood activated Carbon is not known to be toxic by ingestion.		
	However, ingestion of largequantities of AC may cause digestive		
	system blockage.		
4.2 Most im	4.2 Most important symptoms and effects, both acute and delayed: No Data Available		
patient exh	on of any immediate medical attention and special treatment needed: If ibits shortness ofbreath, choking, powder inundated eyes or mouth; medical attention may be required.		

Section 5 - Fire Fighting Measures

Section 5 The Highling Me	
5.1 Extinguishing Media	Dry chemical extinguisher, water, sand, limestone powder,
5.2 Special Hazards	Activated carbon can absorb atmospheric oxygen, especially when wet, resulting in a reduced local oxygen concentration. In confined spaces this may result in locallevels of oxygen below that required to support life. Under these conditions immediate asphyxiation and death is possible. Activated carbon presents a confined-spaces hazard with respect to oxygen depletion.
	Activated carbon may react exothermically with certain
	organic compounds, ketones for example.
Products of Combustion	Carbon dioxide (CO2), Carbon monoxide (CO)
5.3 Advice for Fire Fighters	: Use self-contained air pack, gloves, safety goggles



EcoFriend Carbon Pvt. Ltd.

Mobile : +91 8799335345

Email : quotation@ecofriendcarbon.com

Web: www.ecofriendcarbon.com

Powder & Granular Wood

Based Activated Carbon

5.4 Additional Information: USA NFP Rating 010

Section 6 – Accidental Release Measures

	Wear approved dust mask, safety goggles, and conventional work gloves.
Methods for Cleaning Up:	Conventional Sweep or vacuum. Avoid creating dusting conditions
96.	

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel: Wear approved dust mask, safety goggles, and conventional work gloves. Use conventional cleanup techniques and avoid creating dust. Vacuum is preferred over sweeping. Be cautious ofslip hazard on wet or dry pedestrian surfaces. Wear a dust mask/respirator to reduce the change of inhaled dust.

6.1.2 For emergency responders: Wear approved dust mask, safety goggles, and conventional work gloves. Samemethodology as for non-emergency personnel (sec 6.1.1)

6.2 Environmental Precautions: Wood Based activated carbon is insoluble and will not pose any soluble ion hazards to the environment. However, good housekeeping practices should be followed and spilled material should be cleaned up, and disposed of in an appropriate manner.

6.3 Methods and material for containment and clean up: No special containment needed other than conventional vacuuming and waste containment. Avoid creating dust.

6.4 Reference to other sections: Not needed

6.5 Additional information: Not needed

Section 7 - Handling and Storage

7.1 Precautions for safe handling

7.1.1 Handling Use conventional methods, but avoid dusting conditions. Provide sufficient exhaust ventilationin areas where dust is created. Wear suitable respiratory protection. Keep powder from contacting eyes.

Activated carbon can absorb atmospheric oxygen, especially when wet, resulting in a reduced local oxygen concentration. In confined spaces this may result in local levels of oxygen below that required to support life. Under these conditions immediate asphyxiation and death is possible. Activated carbon presents a confined-Spaces hazard with respect to oxygen depletion.

7.2 Conditions for safe storage, including any incompatibilities.

Storage: Store all carbonaceous materials in a dry location. Keep packaging closed or covered. Store awayfrom heat or flame.

Incompatibilities: Activated carbon is incompatible with all oxidizing agents and certain organic substances.

Dust Explosibility Hazards: Very finely divided activated carbon powder poses a slight risk of dust explosionhazard: Dust class ST1, MIE greater than 10 J (very low hazard of spark ignition)



Based Activated Carbon

EcoFriend Carbon Pvt. Ltd.

Mobile : +91 8799335345

Email : quotation@ecofriendcarbon.com

Web: www.ecofriendcarbon.com

Section 8 – Exposure Controls/ Personal Protection:

8.1 Control parameters

0.1 Control parameter	3			
8.1.1 Occupational exposure limits				
Component	CAS No.	%	ACGIH TWA	Control Reference
Wood Based activatedcarbon	7440- 44-0	10 0	3.0 mg/m ³ Respirable dust 10.0 mg/m ³ Inhalable dust	2014 ACGIH TLV Handbook: Recommendations for insolubleor poorly soluble materials of low toxicity
Engineering Measures	Use adequate dust collection to maintain dust levels below the control orrecommended values.			
Respiratory Protection	Approved dust mask, type N95 recommended.			
Eye Protection	Conventional safety glasses or goggles.			
Skin Protection	Conventional work gloves and clothing.			
Additional	Be aware of confined space hazards(see section 7.1.1)			

8.2 Exposure controls

- 8.2.1 Appropriate engineering controls: Use adequate dust collection to maintain dust levels below the controlor recommended values.
- 8.2.2 Personal protective equipment
- 8.2.2.1 Eye/Face Protection: Wear laboratory goggles, or full side shielded safety glasses.
- 8.2.2.2 Skin Protection: Conventional work gloves and clothing.
- 8.2.2.3 Respiratory Protection: Approved dust mask, type N95 recommended.
- 8.2.3 Environmental exposure controls: Wood based activated carbon is inert and insoluble. To the best of ourknowledge, wood based activated carbon does not present any environmental hazards. No special environmental exposure controls, other than standard practices for dust and spill control, are required. "Used" Activated carbon may have toxicity properties similar to the adsorbate.

Section 9 – Physical and Chemical Properties: 9.1 Information on basic physical and chemical properties

Color:	Gray to Black	Material State	Solid, granular or powder
Odor	None		
Boiling Point:	NA	Melting Point	Sublimates at 3652C
Specific Gravity	1.5-1.9	Vapor Density	Not applicable
Vapor Pressure (mmHg)	NA	% Volatile (By Wt.)	0-8% (non-VOC)
(IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII			
Solubility in Water	Insoluble	Evaporation Rate:	Not applicable
рН	9-11	Auto Ignition	Above 500 °C
Decomposition	Oxidizes above 400C	Dust Explosion class	ST1=KST>0-200 bar m/s,
Temp			MIE above 10 J.
Flash Point	NA Solid substance with	very high melting poir	nt.



EcoFriend Carbon Pvt. Ltd.

Mobile : +91 8799335345

Email : quotation@ecofriendcarbon.com
Web : www.ecofriendcarbon.com

Powder & Granular Wood

Based Activated Carbon

Section 10 - Stability and Reactivity

Section 10 Stability	•
10.1 Reactivity	Wood based activated carbon is non-reactive under ambient conditions.
10.2 Stability	Stable. Will not polymerize or self-react spontaneously.
10.3 Possibility	None known
of hazardous	
reactions	
10.4 Conditions to Avoid	Avoid contact with oxidizing agents. Wood based activated carbon will begin tooxidize at temperatures above 400 C.
10.5	Oxidizing agents. Activated carbon may react exothermically with
Incompatible	certain organiccompounds, ketones for example
materials	
10.6	Carbon Dioxide (CO2), Carbon Monoxide (CO)
Hazardous	
products of	
decomposition	
Flammable	LEL and UEL values not available: Minimum Ignition Energy (MIE)
Limits(% by	greater than 10 joules. When exposed to extremely high energy ignition sources very finely dividedwood based activated carbon powder can
Vol.)	form explosive mixtures with air. Avoid contact between wood based
,	activated carbon dust clouds and high energy ignitionsources.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Acute toxicity: Data/information on acute toxicity of wood based activated carbon is not available. This materialhas low toxicity and is not expected to have any acute toxicity.

STOT-single exposure: Not available.

STOT-repeated exposure: Not available

Aspiration hazard: Solid substance. Based on available data the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics.

Aspiration hazard: Solid substance. Based on available data the

classification criteria are not met. Symptoms related to the physical,

chemical and toxicological characteristics

<u>In case of ingestion:</u> wood based activated carbon is non-toxic and is not expected to be an ingestion hazard.<u>In case of skin contact:</u> Mechanical irritation only is expected.



EcoFriend Carbon Pvt. Ltd.

Mobile : +91 8799335345

Email : quotation@ecofriendcarbon.com
Web : www.ecofriendcarbon.com

Powder & Granular Wood

Based Activated Carbon

<u>In case of inhalation:</u> Usual signs after inhalation of poorly soluble dusts with low toxicity are the only effects expected. No symptoms are expected if relevant occupational exposure levels are complied with. In situations of repeated excessive lung overload due to a high airborne concentration of particles of respirable size for extended periods of time pneumoconiosis may develop. See section 4 for first aid measures.

<u>In case of eye contact:</u> No irritation other than mechanical irritation is expected. No human data on effects aftereye contact is available. See section 4 for first aid measures.

Section 12 - Ecological Information

Section 12 Leologic	a information	
12.1 Toxicity:	Wood based activated carbon is inert and insoluble. To the best of our	
	knowledge, wood based activated carbon does not present any	
	significant environmental hazards.	
	city: Wood based activated carbon is not water soluble and does not	
	on hazard. Fine wood based activated carbon particles suspended in	
	es may be harmful toorganisms sensitive to suspended solids.	
12.1.2 Sediment to	dicity: None known.	
12.1.3 Terrestrial to	xicity: None known.	
12.2 Persistence an	d degradability: Wood based activated carbon is a reduced form of	
carbon and will no	t degrade further under normal conditions. This form of carbon is	
stable, unreactive in	n water under ambient conditions, and is insoluble.	
12.3 Bioaccumulation	on potential: There is no evidence indicating that wood based	
activated carbon is	bio accumulative.	
12.4 Soil Mobility: V	Vood based activated carbon is not expected to have mobility in soil	
as it is an insoluble,	inorganic substance.	
12.5 PBT and vPvB a	assessment: Wood based activated carbon is not a persistent bio	
accumulative and to	oxicsubstance.	
12.6 Other adverse effects: None known. Wood based activated carbon has no ozone		
depleting potential.		

Section 13 – Disposal Considerations:

Dispose of in a manner which conforms to local, state and Federal regulations.

Wood based activated carbon is a reduced form of carbon. Wood based activated carbon is non-hazardousbut disposal of waste should be handled in a responsible matter. Wood based activated carbon is a form of elemental carbon so it is not biodegradable.

Provision of a European Waste Catalog, waste code number, should be handled in agreement with the regionalwaste disposal company.

Packaging should be completely emptied of contents and disposed of in a manner specified by the recycler/regional disposal contractor. Dust formation from packaging residues should be avoided. Store emptypackaging in a suitable receptacle



Based Activated Carbon

EcoFriend Carbon Pvt. Ltd.

Mobile : +91 8799335345

 ${\sf Email} \quad : {\sf quotation@ecofriendcarbon.com}$

Web: www.ecofriendcarbon.com

Section 14 – Transport Information

14.1 UN Number	Not applicable
14.2 UN Proper shipping name	Not applicable
14.3 Transport hazard class	Not applicable
14. 4 Packing Group	Not applicable
14.5 Environmental hazards	None known
Marine Transport	Not classified as a hazardous material
Land Transport	Not classified as a hazardous material
Air Transport	Not classified as a hazardous material per IATA
Transport Label Required	No label required
Additional Transport Information	Note that a representative sample of this activated
iniormation	carbon material was selected and tested per UN test
	methods/UN Recommendation of the Transport of
	Dangerous Goods, 9thEdition for "self-heating"
	properties. Testing results indicated that this material
	has passed the "TEST FOR SELF HEATING SUBSTANCES"
	as reflected in theUJ\J Manual of Tests and Criteria as <u>a</u>
	non self-heating substance.
	As a result of this testing no UN number is required for this non-hazardous activated carbon product (Reference: RD 18010)

Section 15 – Regulatory Information

15.1 Regulatory Status and Inventories

Not Classified		
Inventory Information:		
EEC EINECS	#231-153-3	
US TSCA	Yes	
Canada DSL	Yes	
Canada NDSL	No	
Australian AICS	Yes	
Korean ECL	Yes	
Asia PAC	Yes	
PICCS	Yes	
New Zealand NZLoC	Yes	
HSNO Approval	HSR001271	
REACH: On list of pre-reg		
	vated carbon is compliant with the EU RoHS directive	
WEEE: Wood based activated carbon is compliant with the EU waste electrical and		
electronic equipmentdirective		
15.2 Chemical Safety Assessment: For this substance a chemical safety assessment is not required		



Mobile : +91 8799335345

 ${\sf Email} \quad : {\sf quotation@ecofriendcarbon.com}$

EcoFriend Carbon Pvt. Ltd.

Web: www.ecofriendcarbon.com

owaci a Granalai Wood

Based Activated Carbon

Section 16 - Other Information

Abbreviations Used:

ACGIH TWA American Council of Government and Industrial Hygienists Time

Weighted Average value.CAS Chemical Abstracts Service

NA Not applicable

N.O.S. Not otherwise specified

BW Body weight

Definitions:

Adsorbate: the substance adsorbed (or absorbed) into the activated carbon surface.

