CHEMBALL

chemball.com

MATERIAL SAFETY DATA SHEE

Version 4.9 Revision Date 06/02/2016 Print Date 08/08/2017

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 **Product identifiers**

Isopropyl acetate

CAS-No. : 108-21-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

> Company detail: CHEMBALL (HANGZHOU) CO.,LTD 1314, Jinjun plaza, Shuixiang Road, Hangzhou, China, 310020

Tel: 0086-571-86539522,FAX:0086-571-86539526

1.4 **Emergency telephone number**

> +1-703-527-3887 (CHEMTREC) Emergency Phone #

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

Highly flammable liquid and vapour. H225 H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statement(s)

Keep away from heat/sparks/open flames/hot surfaces. No smoking. P210

P233 Keep container tightly closed.

Ground/bond container and receiving equipment. P240

Use explosion-proof electrical/ ventilating/ lighting/ equipment. P241

Use only non-sparking tools. P242

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for

breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to

extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Synonyms : IPrOAc

Hazardous components

Component		Classification	Concentration
Isopropyl acetate			
	C.C.	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319,	<= 100 %
		H336	

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eve contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Moisture sensitive.

Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Isopropyl acetate	108-21-4	TWA	250.000000 ppm 950.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	Remarks	The value in	mg/m3 is approxir	nate.

TWA	100 ppm	USA. ACGIH Threshold Limit Values (TLV)
Upper Respi	vous System impaii iratory Tract irritation	
TWA	100.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation		
STEL	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation		
STEL	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation		
See Appendix D - Substances with No Established RELs		
See Appendix D - Substances with No Established RELs		
TWA	250 ppm 950 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
The value in mg/m3 is approximate.		
PEL	250 ppm 950 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
STEL	310 ppm 1,185 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 120 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an

industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Impervious clothing. Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Form: liquid

Colour: colourless

b) Odour pleasant, aromatic

Odour Threshold No data available c) d) No data available

рH

Melting point/freezing e)

point

Melting point/range: -73 °C (-99 °F) - lit.

f) Initial boiling point and

boiling range

85 - 91 °C (185 - 196 °F) - lit.

g) Flash point 4 °C (39 °F) - closed cup

h) Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit: 8 %(V) Upper/lower flammability or Lower explosion limit: 1.8 %(V) explosive limits

63 hPa (47 mmHg) at 20 °C (68 °F) Vapour pressure

3.53 - (Air = 1.0)Vapour density m) Relative density 0.872 g/cm3

Water solubility 31.9 g/l at 20 °C (68 °F) - soluble

Partition coefficient: n

octanol/water

log Pow: 1.28 at 20 °C (68 °F)

Auto-ignition 460 °C (860 °F) at 1,013 hPa (760 mmHg) temperature

Decomposition temperature

No data available

No data available r) Viscosity No data available s) Explosive properties Oxidizing properties No data available

9.2 Other safety information

> Relative vapour density 3.53 - (Air = 1.0)

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

acids, Bases, Oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 6,750 mg/kg

LC50 Inhalation - Rat - 8 h - 50,600 mg/m3

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

reverse mutation assay

S. typhimurium

Result: negative

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Al4930000

prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish static test LC50 - Leuciscus idus melanotus - 265 mg/l - 48 h

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 20 d

Result: 100 % - Readily biodegradable

(OECD Test Guideline 301D)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1220 Class: 3 Packing group: II

Proper shipping name: Isopropyl acetate

Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 1220 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ISOPROPYL ACETATE

IATA

UN number: 1220 Class: 3 Packing group: II

Proper shipping name: Isopropyl acetate

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Isopropyl acetate	108-21-4	1993-04-24

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Isopropyl acetate	108-21-4	1993-04-24

New Jersey Right To Know Components

	CAS-No.	Revision Date
Isopropyl acetate	108-21-4	1993-04-24

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit. Eye irritation Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Health hazard: 2
Chronic Health Hazard:
Flammability: 3
Physical Hazard 0

NFPA Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

Further information

Copyright 2016 CHEMBALL Co. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product.

Version: 4.9 Revision Date: 06/02/2016 Print Date: 08/08/2017