

HTDA Product technical specification

Product name: 4-Methylcyclohexane-1,3-Diamine

Compilation date: September 08, 2020

product use

Colorless or slightly yellow, transparent liquid.

Structural adhesive; paving, sizing, external coating, etc.; composite lining; casting and packaging.

performance index

project	metric	unit	test method
surface	Transparent, with no mechanical impurities	-	visualization
smell	No odor	-	-
tone	≤ 1	Gardner	visualization
amine value	820-880	mg KOH /g	titration
Shuifen	≤ 900	ppm	chromatography of gases

packing specifications

HDPE ton 900kg / barrel

Storage considerations:

Store in a cool, ventilated warehouse. The library temperature should not exceed 40°C. Should be stored separately with oxidants and edible chemicals, and avoid mixed storage. Suitable for container materials: glass, high-density polyethylene. Keep the container sealed. Stay away from the fire and heat sources. The warehouse must be installed with lightning protection equipment. The exhaust system shall be equipped with a grounding device to remove static electricity. Explosion-proof lighting and ventilation setting

are used. No spark prone equipment and tools. The storage area shall be equipped with leakage emergency treatment equipment and suitable shelter materials.

The indicators and data given in this data are based on our existing technical knowledge level and practical experience and are for reference only. The specific guarantee index shall be subject to the provisions of the quality guarantee certificate or the supply contract.

Address: 1 km west of the intersection of Jianshe Road and Puyang Road, Puyang City, Henan Province zip code: 450001

Tel. : 0393-6612882 Fax: 0393-4471239

Enterprise emergency telephone number: 0393-6612882- (24h)