



HENAN KAILUN CHEMICAL CO.,LTD

Add: Lijiang East Rd,Huaxian Industrial Agglomeration Area,Henan ,China

Tel: 0086-372-8112391 / 0086-18567812865 Fax: 0372-372-8112724

Website: www.kailunchem.com Email: jackyliu@kailunchem.com

Technical Data Sheet

Rubber Accelerator TMTD (TT)

CAS No. : 137-26-8

Chemical Name : Tetramethylthiuram Disulfide

Technical Specification :

Item	Technical Specifications
Appearance	White,light gray powder or granular
Melting Point °C /min.	140.0
Loss on Heating % max.	0.30
Ash Content % max.	0.30
Residues on 150µm sieve % max.	0.10
Purity % min.	96.0

Properties :

White, light gray powder or granular. The density is 1.29 soluble in benzene, acetone, chloroform, CS₂, partly soluble in alcohol, diethyl ether, CCl₄ insoluble in water, gasoline, and alkali with lower concentration. Meeting hot water becomes to dimethylamine ammonium and CS₂ is sensitive to skin and respiratory tract

Application :

Be used as a super vulcanization accelerator,usually used in combination with thiazole acelerae or a vulcanization of continuously sizing material when use in manufacturing tire inner tube,rubber overshoes,cable etc.Also be used as bactericide and pesticide in agriculture and lubricant aditive.

Package :

In woven bag or kraft paper bag lined with PE film bag.

Net weight: 25Kg/bag.

Storage :

The product should be stored in a dry and cooling place with good ventilation.

Validity Period : 1 years.

Precaution :

Please refer to the appropriate material safety data sheet (MSDS) prior to Using this product.

FOR INDUSTRIAL USE ONLY.

Disclaimer :

All information on this data sheet is based on laboratory testing and is not Intended for design purposes.