

## 高强高模聚乙烯醇纤维 W2 (超短纤)

分子式:  $(\text{CH}_2\text{CHOH})_n$

质量标准: 纤度:  $2.0 \pm 0.25 \text{ dtex}$

强度:  $\geq 12.80 \text{ CN/dtex}$

伸度:  $\leq 7\%$

模量 (0.1-0.4%):  $\geq 290 \text{ CN/dtex}$

热水减量 (90℃, 1 小时):  $\leq 2\%$

比重: 1.29

切断长度: 4mm, 5mm, 6mm

包 装: 180 公斤净重塑编袋 (1000×550×600mm)  
12.96 吨/20'FCL 集装箱

用 途: 石棉代用品;  
用于建材、混凝土业等领域;  
可用做塑料、橡胶的增强纤维。

安徽皖维高新材料股份有限公司

地址: 中国安徽省巢湖市皖维路 56 号 国际贸易部

电话: 0551-82189233

传真: 0551-82317233

邮政编码: 238002

## HIGH STRENGTH AND HIGH MODULUS POLYVINYL ALCOHOL FIBER W2 (OVERSHOTR)

Formula:  $(\text{CH}_2\text{CHOH})_n$

Quality Standard: Count:  $2.0 \pm 0.25 \text{ dtex}$

Tenacity:  $\geq 12.80 \text{ CN/dtex}$

Elongation:  $\leq 7\%$

Molulus (0.1-0.4%):  $\geq 290 \text{ CN/dtex}$

Hot Water Solubility(90℃, 1hour):  $\leq 2\%$

Density: 1.29

Cut Length: 4mm, 5mm, 6mm

Packing: P.P. bag, 180kg net weight  
(1000×550×600mm)

12.96T/20'FCL Container

Uses: It is the best substitution of asbestos, used in the building material industry, concrete industry and so. It also can increase intensity of plastic and rubber.

ANHUI WANWEI UPDATED HIGH-TECH MATERIAL  
INDUSTRY COMPANY LIMITED

Add: No. 56 Wanwei Road, Chaohu City, Anhui Province, China

Tel: 0551-82189233

Fax: 0551-82317233

Post Code: 238002